

Technische Daten

Schutzart	IP 67
Umgebungstemperatur	0°C / +60°C
Gewicht	535 g
Gehäusematerial	PUR

Bus-System

ID-Nummer	06EA hex
GSD-Datei	Lum_06EA.gsd
Übertragungsrate	max. 12 Mbaud
Adressbereich	1–126 dez
Drehadressierschalter	1–99 dez
Voreingestellte Adresse	99 dez

Elektronik-Stromversorgung

Nennspannung	24 V DC
Spannungsbereich	19–30 V DC
Stromaufnahme	typ. 60 mA
Verpolschutz	ja
Anzeige	LED grün

Aktorik-Stromversorgung

Nennspannung	24 V DC
Spannungsbereich	19–30 V DC
Potentialtrennung	vorhanden
Verpolschutz	ja/Antiparalleldiode
Anzeige	LED grün

Ausgänge

Nennausgangsstrom	0,7 A pro Kanal
Kurzschlussfest	ja
Max. Strombelastbarkeit	11,2 A pro Modul
Überlastfest	ja
Anzahl der digitalen Kanäle	16
Kanaltyp Schließer	p-schaltend
Statusanzeige	LED gelb pro Kanal
Diagnoseanzeige	LED rot pro Kanal

Lieferumfang / Zubehör

M12-Schutzkappen	2 Stück
Beschriftungsschilder	10 Stück

Anschlusshinweis

siehe Übersichtsseite

Technical data

Degree of protection	IP 67
Operating temperature range	0°C / +60°C
Weight	535 g
Housing material	PUR

Bus system

ID number	06EA hex
GSD file	Lum_06EA.gsd
Transmission rate	max. 12 Mbaud
Address range	1–126 dez
Rotary address switches	1–99 dec
Default address	99 dec

Electronics power supply

Rated voltage	24 V DC
Voltage range	19–30 V DC
Power consumption	typ. 60 mA
Reverse polarity protection	yes
Indication	LED green

Output power supply

Rated voltage	24 V DC
Voltage range	19–30 V DC
Potential separation	present
Reverse polarity protection	yes/antiparallel diode
Indication	LED green

Outputs

Rated output current	0.7 A per channel
Short-circuit proof	yes
Max. output current	11.2 A per module
Overload-proof	yes
Number of digital channels	16
Channel type N.O.	p-switching
Channel status indicator	LED yellow per channel
Diagnostic indication	LED red per channel

Included in delivery / accessories

Dust covers M12	2 pieces
Attachable labels	10 pieces

Connecting information

please see overview

Bestellbezeichnung Designation

0970 PSL 215

